

Titan power in a compact 8U console.

Access powerful Titan control in our smallest ever portable console. Powered by Titan, D3-010 supports 8 universes without a laptop: just add a monitor and you're ready to go. Built for live environments, D3-010 is compact, tough, travel-ready, and performs straight out of the case.



Control surface.

EXTERNAL SCREENS	1x up to 4K (UHD)
SURFACE LAYOUT	Compact layout (reduced version of D7 & D9 layouts)
PLAYBACK FADERS	10x 60mm faders
FLASH BUTTONS	20x C&K buttons with custom cap
PROGRAMMING / SETUP KEYS	76x backlit Cherry MX Low Profile keys
PLAYBACK PAGING KEYS	3x backlit Cherry MX Low Profile keys
PLAYBACK CONTROL KEYS	5x backlit Cherry MX Low Profile keys, incl. double-width Go key
MACRO/EXECUTOR KEYS	12x backlit Cherry MX Low Profile keys
ATTRIBUTE CONTROL WHEELS	3x high resolution, metal Avo encoders with select buttons
USB WING SUPPORT	1x D3 Wing, T3 Wing, or Titan Mobile Wing
D3 TOUCH SUPPORT	Yes (unlimited)
MOBILE APP	Yes - iOS & Android ("Titan Remote")

Software.

SOFTWARE PLATFORM	Avolites Titan	CONTROL PROTOCOLS	DMX512 (E1.11) Streaming ACN (E1.31) Art-Net & Art-RDM CITP GDTF (through Capture) SMPTE LTC MIDI over USB (MIDI Notes & MTC) Web API
BUILT IN 3D VISUALISATION	Capture Engine		
DMX UNIVERSES PER DEVICE	8 universes (4,096)		
DMX UNIVERSES PER SYSTEM	8 universes (4,096)		
MAX FIXTURES	Unlimited		

TitanNet.

EXPAND PROCESSING	No	MULTI-CONSOLE SESSION	Yes
OFFLOAD PROCESSING	Yes		

Connectivity.

EXTERNAL MONITOR	1x USB-C or DisplayPort	USB 3.2 GEN1 (DP ALT MODE)	1x USB-C (rear)
GIGABIT ETHERNET	2x RJ45	USB 3.2 GEN1	3x USB-A (1x side, 2x rear)
DMX (IN & OUT)	4x Neutrik 5-pin XLR	SMPTE LTC INPUT (BALANCED)	1x Neutrik 3-pin XLR (incl. signal indicator)

Physical.

WEIGHT	4.6 kg	DIMENSIONS (W x D x H)	398 x 275 x 78 mm
PACKAGED WEIGHT	TBC	PACKAGED DIMENSIONS	575 x 343 x 149 mm
PACKAGING	Cardboard		

Hardware.

OPERATING VOLTAGE	100-240V AC, 50/60Hz	POWER CONSUMPTION	130W max
CURRENT	2.4A - 1.1A	HEAT OUTPUT	TBC
POWER CONNECTOR	Neutrik PowerCON TRUE1	IP RATING	IP20 (indoor use only)
POWER SWITCH	Yes	OPERATING TEMPERATURE	0-40°C
SOFT POWER BUTTON	Yes	HUMIDITY	95% non-condensing

Certification and Safety.

CONFORMITY	CE, WEEE, RoHS
------------	----------------

Part Number.

30-02-3010	D3-010 Includes console cover, power cable, recovery stick & 2-year return to base warranty
------------	--

Accessories.

8100-9302	D3-010 or D3 Wing Dust Cover
09-01-3010	D3-010 or D3 Wing Peli Case