D3 Touch. DATASHEET.

Remotely trigger Titan from a reliable touchscreen.

designed for venues and installations where presets. Fully integrated with Titan, it's plug-and-



Control surface.

INTERNAL SCREENS

Software.

SUPPORTS

4x Titan Playback Groups - User Numbers 1001 - 1004. (More can be added using Macros to change User Numbers). **ZONES**

SCENES PER ZONE

MACROS

LOCK SCREENS

UNLOCK CODE

Connectivity.

GIGABIT ETHERNET

Physical.

WEIGHT DIMENSIONS (W x D x H)

PACKAGED WEIGHT PACKAGED DIMENSIONS

PACKAGING MOUNTING DEPTH



SUPPORT@AVOLITES.COM



D3 Touch. DATASHEET.

Hardware.

POWER CONNECTOR (POE) SOFT POWER BUTTON

POWER CONNECTOR (PSU) IP RATING

POWER CONSUMPTION **OPERATING TEMPERATURE** 0-40°C

HUMIDITY

Certification and Safety.

CONFORMITY

Part Number.

30-02-3005

PSU (100-240VAC, 50/60Hz, 0.6A)

Mounting bracket for panel/pattress mounting (incl. 6x screws)

2 pin Pluggable screw terminal block (3.81mm pitch)

3 pin Pluggable screw terminal block (3.81mm pitch - for future use)

2-year return to base warranty

Accessories.

TBC

